


INSTALLATION INSTRUCTIONS

SINGLE HANDLE KITCHEN FAUCET W/SPRAY

廚房單槍龍頭(附:噴槍)安裝說明



CAUTION : Prevent The Risk of Product Damage.

注意：為增加產品使用壽命，請依說明清潔供水管路。

a./ Turn the angle stops (water suppliers) on and run for 1 minute before connect supply hose (flexible hose) to faucet body. or b./

安裝編織管之前，先把供水開關全開排水一分鐘。或 b./

b./ Connect and tighten the faucet and angle stops with supply hose (flexible hose) to finish installation, then remove the aerator, fully turn on the hot and cold water valves on faucet and run for 1 minute, then turn off the water and reinstall the aerator.

把龍頭、供水開關及編織管接好並鎖緊之後，把起泡器移開，把熱水及冷水全部轉開一分鐘，然後把水關掉再把起泡器裝回去。

Faucet Installation: a. Screw **Flexible Hoses (with seal O-RING)** and **Mounting Bolt** into **Faucet Body**.

龍頭安裝說明:

將冷熱進水不銹鋼軟管和金屬牙條鎖緊固定於龍頭本體。

b. Insert **Flexible Hoses** and **Mounting Bolt** through deck hole in fixture.

再將冷熱進水不銹鋼軟管和金屬牙條穿過檯面洞口後，準備安裝，

c. Place **Bracket (with Bracket Washer)** and **Nut** onto **Mounting Bolt**, position faucet on fixture, and then tighten **Nut** securely.

從金屬牙條下方依序套入橡皮墊片、金屬固定片、和螺帽，確認龍頭方向位置後，鎖緊螺帽固定龍頭即可。

d. Connect **Flexible Hoses** to water supplies.

連接冷熱進水不銹鋼軟管到進水開關，確認完成安裝程序。

Spray Installation: a. Remove the **Lock Nut** from the **Spray Escutcheon** first, insert the **Spray Escutcheon**

噴槍安裝說明:

into the deck hole and tighten the **Lock Nut** to secure the **Spray Escutcheon** in place.

將噴槍底座上的螺帽鬆開，然後將噴槍底座穿過檯面洞口，鎖緊螺帽固定噴槍底座。

b. Connect the **Spray Hose** to **Spray**, insert the Hose through the **Spray Escutcheon** and connect it to **Faucet Hose-outlet** securely.

組合噴槍軟管與噴槍，並連結鎖緊噴槍軟管與龍頭小軟管接頭。

FIXING CONTENTS

組配件內容

